



YOU NEED TO MEASURE THIS

CENTER OF THE HITCH PIN HOLE TO THE OUTSIDE OF THE SPARE TIRE

EXAMPLE:

The outside of your spare tire to the center of the hitch pin hole is **12"**

12" minus **9"** = **3"** plus **3" clearance** = **6"**

If your tire measures 12" to pin you will want to select **+6" Longer Main Bar**

YOU WANT 2" - 4" CLEARANCE

BIKES FOOT PEGS 20" ACROSS

THIS AQUA RECTANGLE REPRESENTS YOUR BIKES FOOT PEGS
APPROXIMATE AVERAGE WIDTH

9"

19.75"
STANDARD LENGTH

OUR STANDARD LENGTH MX MAIN BAR IS:
HITCH PIN HOLE TO CENTER BIKE = 19.75"
HITCH PIN HOLE TO BIKES INSIDE PEG = 9"

RACK N RIDE HITCH MOUNTED MOTORCYCLE CARRIER MX MAIN BAR STANDARD DIMENSIONS

HOW TO SELECT THE CORRECT LENGTH MAIN BAR FOR YOUR SUV WITH A REAR MOUNTED SPARE TIRE OR OTHER ACCESSORIES

ALL COPYRIGHT AND OTHER PROPERTY RIGHTS CONTAINED HEREIN ARE THE PROPERTY OF RACK N ROLL PTY LTD AND ARE NOT TO BE COPIED, REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN CONSENT OF RACK N ROLL PTY LTD

© RACK N ROLL PTY LTD