YOU NEED TO MEASURE THIS

?"

CENTER OF THE HITCH PIN HOLE
TO THE OUTSIDE OF THE SPARE TIRE

EXAMPLE:

The outside of your spare tire
to the center of the hitch pin hole is 12"

12" minus 10" = 2" plus 4" clearance = 6"

If your tire measures 12" to pin you will want to select
6" + 9" HITCH EXTENDER

YOU WANT 2" - 4" CLEARANCE

BIKES FOOT PEGS 20" ACROSS

THIS AQUA RECTANGLE REPRESENTS YOUR BIKES FOOT PEGS

APPROXIMATE AVERAGE WIDTH

9"

20"

STANDARD LENGTH

OUR STANDARD LENGTH SPORT MAIN BAR IS:

HITCH PIN HOLE TO CENTER OF BIKE = 20"

HITCH PIN HOLE TO BIKES INSIDE PEG = 9"

RACK N RIDE SPORT MOTORCYCLE CARRIER - HITCH TUBE STANDARD DIMENSIONS

HOW TO SELECT THE CORRECT LENGTH HITCH TUBE FOR YOUR SUV WITH A REAR MOUNTED SPARE TIRE OR OTHER ACCESSORIES

ALL COPYRIGHT AND OTHER PROPERTY RIGHTS CONTAINED HEREIN ARE THE PROPERTY OF RACK N ROLL PTY LTD AND ARE NOT TO BE COPIED, REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN CONSENT OF RACK N ROLL PTY LTD

© RACK N ROLL PTY LTD